

KPS Global provides replacement doors that are manufactured to fit any brand of walk-in on the market. To order your new replacement door, fill out the below and email to parts@kpsglobal.com.



TELL US ABOUT YOUR EXISTING DOOR: (check all that apply)

FLUSH-MOUNT DOOR



OFFSET/INSET DOOR



BRAND/SERIAL NUMBER: _____

EXISTING HINGES: IN-SWING (inside hinges) STANDARD (outside hinges)


EXISTING RAISED INSULATED FLOOR:

N/A YES (floor thickness: _____)


EXISTING RAMP: N/A INTERIOR RAMP EXTERIOR RAMP

CHOOSE FROM THREE REPLACEMENT DOOR KIT OPTIONS:


For more information on our door kits, view our Replacement Walk-in Doors video at kpsglobal.com/doors.



- DOOR WITH OUTSIDE FACE FRAME KIT
- OUTSIDE FACE FRAME ONLY (no door)



- DOOR WITH OUTSIDE & INSIDE FACE FRAME KIT
- INSIDE & OUTSIDE FACE FRAMES ONLY (no door)



- DOOR WITH FULL RETROFIT KIT*
- FULL RETROFIT KIT ONLY* (no door)

*NOTE: Once installed, the full retrofit kit will reduce the door opening width by 4" and height by 2".

FOLLOW THE BELOW FIVE STEPS TO A NEW REPLACEMENT DOOR:

STEP 1 Is it a cooler or freezer?

COOLER FREEZER

STEP 2 Left or right hinge?

LEFT HINGE RIGHT HINGE
Quantity: 2 3 4

STEP 3 Measure the wall thickness.*

Existing wall thickness: _____

STEP 4 Provide the narrowest dimensions for the width and height of the door opening.*

Width: _____ Height: _____
 Finished Opening Rough Opening

STEP 5 Specify what options you'd like:

VIEWPORT WINDOW N/A YES (14"x14") YES (14"x24") WITH HEAT

KICKPLATES INTERIOR EXTERIOR

Height: _____ Finish: DTA GALVANIZED STEEL

JAMB GUARDS** GALVANIZED STEEL

FINISHES

Interior: NATURAL (gray) WHITE STAINLESS STEEL OTHER _____

Exterior: NATURAL (gray) WHITE STAINLESS STEEL OTHER _____

REPLACEMENT PARTS THRESHOLD THERMOMETER

3-WAY LIGHT SWITCH WITH PILOT LIGHT BUMPER GUARD OTHER _____

*View our How to Measure video tutorial at kpsglobal.com/doors.

**All door kits ship complete with 18-gauge steel adjustable jamb guards.